breccie
STEENHOUWERIJ

USER INFORMATION 15.5 - Quartz composite

Dear customer,

In order to fully enjoy your quartz composite, we give you the following recommendations for protection and maintenance.

1. FLOORS AND LARGE AREAS:
A first and once-only treatment with 'Lithofin **MN Protector Composiet**' is allowed if you choose a porous finish, except for Silestone. See custom made work.

Frequent cleaning:
For a continuous maintenance of the floor use 'Lithofin **MN Wash & Clean**'.

'Lithofin **MN Wash & Clean**': add a little bit of some 20g to 10l of lukewarm mop water, mop thoroughly, do not rinse, but wipe with a wrung out cloth.

Do not use too much product or soap, as this will leave a film.

Bij sterke vervuiling: van bijvoorbeeld aarde, stof, …
Gebruik Lithofin **MN Vuiloplosser**, sterk verdund in water 1:10, NIET laten opdrogen en met zeer veel water naspoelen.

In case of heavy soiling: from for example soil, dust,…
Use 'Lithofin **MN Vuiloplosser**', strongly diluted in water 1:10, DO NOT let dry and rinse with plenty of water.

2. CUSTOM MADE WORK
Daily maintenance with 'Lithofin **MN Easy Clean**' or 'Silestone **Q-Action**' , apply with a wet sponge or microfibre cloth and dry.

Protection:
A first and ONLY treatment with 'Lithofin **MN Protector Composiet**' is allowed, except for Silestone.
Apply the **stain stop** pure on a CLEAN and DRY surface with a cotton rag or a new roll (for larger surfaces). Do not leave any puddles and rub in well within 15 minutes. Do not make wet for 24 hours, so that the product is not "rinsed away".

The manufacturer of Silestone strongly advises against the use of 'Lithofin **MN Protector Composiet**'. Any manufacturer of quartz composite does not recommend using stain stop a second time or later.

PAY ATTENTION!
Quartz composite is HEAT SENSITIVE: hot cooking pots, hot frying fat,… can stain.
Highly aggressive products such as Viakal, Antikal, plunger,… can also stain.
Stains on/in quartz composite can no longer be removed or treated.

breccie
STEENHOUWERIJ

For custom-made products, we seal joints with elastic marble silicone; the durability of this strongly depends on maintenance and daily use. The reapplication of the joint silicone is not part of the guarantee.

IN CASE OF LIMESCALE POLLUTION:
Wet your stone and spray with 'Lithofin **MN Easy Clean'**, use stainless steel wool WET to mechanically remove lime traces. If necessary, use a little Cif Cream (yellow packaging) or 'Lithofin **MN Vuiloplosser'** diluted or 'Akemi **Steenreiniger'**. Always rinse with plenty of water. If necessary, reapply the stain protection.

For other stains, please consult our FAQ section WHAT TO DO ABOUT STAINS?

Stain stop:
Lithofin **MN Protector Composiet** for dull, rough and polished surfaces

Always follow the instructions on the packaging of your product